



# GLSH

## COURBES DE POMPAGE MODÈLE GLSH

CAPACITÉ EN GALLONS PAR MINUTE

Modèle	Moteur C.V. (kW)	Pression Refolement P.S.I. (kPa)	Profondeur en Pieds (Mètres)				
			5 (1.52)	10 (3.05)	15 (4.57)	20 (6.10)	25 (7.62)
			Capacité - U.S. Gallons par Minute (Litres par Minute)				
GLSH-75	3/4 (.55)	10 (69)	52 (197)	49 (185)	45 (170)	41 (155)	35 (132)
		20 (138)	46 (174)	44 (166)	40 (151)	36 (136)	30 (113)
		30 (207)	39 (147)	35 (132)	30 (113)	25 (95)	19 (72)
GLSH-100	1.0 (.75)	10 (69)	56 (212)	52 (197)	49 (185)	45 (170)	37 (140)
		20 (138)	52 (197)	48 (181)	45 (170)	40 (150)	32 (121)
		30 (207)	45 (170)	40 (151)	37 (140)	30 (113)	22 (83)
		40 (276)	20 (76)	14 (53)			
GLSH-150	1.5 (1.1)	10 (69)	63 (238)	59 (223)	55 (208)	50 (189)	39 (148)
		20 (138)	58 (219)	55 (208)	51 (193)	46 (174)	35 (133)
		30 (207)	53 (200)	50 (189)	45 (170)	40 (150)	26 (98)
		40 (276)	32 (121)	26 (98)	13 (49)		
GLSH-200	2.0 (1.5)	10 (69)	74 (281)	70 (266)	66 (248)	59 (224)	47 (179)
		20 (138)	71 (268)	68 (258)	62 (236)	56 (212)	44 (166)
		30 (207)	64 (241)	61 (229)	56 (212)	51 (192)	39 (147)
		40 (276)	44 (168)	38 (143)	26 (99)		

Modèle	GLSH-75	GLSH-100	GLSH-150	GLSH-200
Débit Nul P.S.I. (kPa)	43 (296)	44 (303)	46 (317)	48 (330)

